

TANDEM AXLE GOOSENECK

G.V.W.R.	14,000#	AXLES	Two 7000# EZ LUBE w/ Elec. Brakes
G.A.W.R. (Ea. Axle)	7,000#	SUSPENSION	Multi-Leaf Slipper Spring w/ Equalizer
COUPLER	2-5/16" Ball Adj. Pipe / 3" ID Pintle on PH	TIRE	ST235/85R16 Load Range E
SAFETY CHAINS	3/8" Grd. 70 w/Safety Latch Hook (2 ea.)	WHEEL	6.00 X 16" HD White Modular - 8 Bolt
JACK	12,000# Drop Leg Jack (Bolted On)	FLOOR	2" Pine
NECK	10" Channel	LIGHTS	D.O.T. Stop, Tail, Turn and Clearance
TOP RAIL	(none)	ELEC. PLUG	7-Way RV
FRAME	12" - 16# I-Beam	FINISH (PREP)	Acid Etched w/White Phosphorus, Undercoated w/Parther 813 & Two Coats Primer
CROSSMEMBERS	3" Channel	FINISH	Painted w/2 Coats High Solid <i>Supreme</i> Acrylic Automotive Grade Enamel, and Pinstriped
SIDE RAILS	6" Channel w/ Rub Rail and		

- 5' Dovetail w/Double Hinged Spring Assist Fold-Over Ramps
- Complete Break-A-Way System w/ Battery & Charger
- Rubber Mounted Sealed Lighting
- Cambered Ez Lube Axles
- Modular Sealed Wiring Harness
- Safety Reflective Marker Tape
- (2) Side Bed Steps
- Spare Tire Mount
- 3/8" Heavy Duty Rub Rail
- 102" Overall Width
- Chain Basket between the gooseneck
- Pintle has Single TW Drop-Leg Jack
- Bolt On Jack w/ Greasable Handle
- Radial Tires on HD Wheels

- Floor Secured w/5/16" Torx Screws

DIMENSIONS - WITH DOVETAIL			
MODEL	A	B	C
20+5	2.40	19.6	44
22+5	2.64	21.6	48
24+5	2.88	23.2	56
26+5	3.12	24.8	64
28+5	3.36	26.4	72

14GN / 14PH



PRICING

MODEL #	WEIGHT	DESCRIPTION	PRICE
14GN-20+5	4825#	102" X 20' +5' Tandem 14,000# Gooseneck/Pintle (14PH)	
14GN-22+5	5085#	102" X 22' +5' Tandem 14,000# Gooseneck/Pintle (14PH)	
14GN-24+5	5440#	102" X 24' +5' Tandem 14,000# Gooseneck/Pintle (14PH)	
14GN-26+5	5795#	102" X 26' +5' Tandem 14,000# Gooseneck/Pintle (14PH)	
14GN-28+5	6155#	102" X 28' +5' Tandem 14,000# Gooseneck/Pintle (14PH)	

OPTIONS

No Dovetail (Straight Deck)	
5' Center Pop-Up Dovetail w/5' Fold-up Ramps	
Torsion Axles	
Square Adjustable Screw Type Coupler	
Dual Drop Leg Jacks (Single Speed)	
Single Two Speed Drop-Leg Jack	
Dual Two Speed Landing Gear Jacks (150K)	
Deck On The Neck (6')	
16" Spare Tire & Wheel	
16" Spare Tire & Wheel - Load Range F	
Tire Upgrade to LT235/85R16 LR "F"	
Low Profile Tool Box 12" X 18" X 36" (Side Mount)	
Tool Box 18" X 18" X 36" (Side Mount)	
L.E.D. Lighting	
Elec./Hyd. Brakes (Drum)	