



	<b>Trail Blazer 8 ft. Wide Tandem Axle</b>			
<b>Model</b>	<b>TB810TA2</b>	<b>TB812TA2</b>	<b>TB814TA2</b>	<b>TB816TA2</b>
Overall Length	13' 10"	15' 10"	17' 10"	19' 10"
Width	8' 6"	8' 6"	8' 6"	8' 6"
Height	8' 6"	8' 6"	8' 6"	8' 6"
Interior Length	10' 7"	12' 7"	14' 7"	16' 7"
Width / BWW	7' 6" / 81"	7' 6" / 81"	7' 6" / 81"	7' 6" / 81"
Height	6' 8"	6' 8"	6' 8"	6' 8"
Rear Door	Double	Double	Double	Double
Width	7'	7'	7'	7'
Height	6'	6'	6'	6'
Hitch Weight	215 lbs.	230 lbs.	245 lbs.	260 lbs.
Height	20"	20"	20"	20"
Ball Size	2-5/16"	2-5/16"	2-5/16"	2-5/16"
Platform Height	20"	20"	20"	20"
G.V.W.R	7,000 lbs.	7,000 lbs.	7,000 lbs.	7,000 lbs.
Curb Weight	2,150 lbs.	2,300 lbs.	2,450 lbs.	2,600 lbs.
Payload	4,850 lbs.	4,700 lbs.	4,550 lbs.	4,400 lbs.
Axles (Tandem)	3,500 lbs.	3,500 lbs.	3,500 lbs.	3,500 lbs.
Brakes	Electric	Electric	Electric	Electric
Tires	ST205/75D14/C	ST205/75D14/C	ST205/75D14/C	ST205/75D14/C
Wheels	5 Bolt	5 Bolt	5 Bolt	5 Bolt
Frame	6" I-Beam	6" I-Beam	6" I-Beam	6" I-Beam
Floor (24" O/C)	3/4" Plywood	3/4" Plywood	3/4" Plywood	3/4" Plywood
Side Walls (16" O/C)	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood

**G.V.W.R.** (Gross Vehicle Weight Rating)

**O/C** (On Center): Refers to the distance between each stud or joist.

**BWW** (Between the Wheel Wells)

Some trailers are shown with optional equipment.

Specifications are based on the latest information and are subject to change without notice.



	<b>Trail Blazer 8 ft. Wide Tandem Axle</b>			
<b>Model</b>	<b>TB818TA2</b>	<b>TB820TA2</b>	<b>TB822TA2</b>	<b>TB824TA2</b>
Overall Length	21' 10"	23' 10"	25' 10"	27' 10"
Width	8' 6"	8' 6"	8' 6"	8' 6"
Height	8' 6"	8' 6"	8' 6"	8' 6"
Interior Length	18' 7"	20' 7"	22' 7"	24' 7"
Width / BWW	7' 6" / 81"	7' 6" / 81"	7' 6" / 81"	7' 6" / 81"
Height	6' 8"	6' 8"	6' 8"	6' 8"
Rear Door	Double	Double	Double	Double
Width	7'	7'	7'	7'
Height	6'	6'	6'	6'
Hitch Weight	275 lbs.	290 lbs.	305 lbs.	320 lbs.
Height	20"	20"	20"	20"
Ball Size	2-5/16"	2-5/16"	2-5/16"	2-5/16"
Platform Height	20"	20"	20"	20"
G.V.W.R	7,000 lbs.	7,000 lbs.	7,000 lbs.	7,000 lbs.
Curb Weight	2,750 lbs.	2,900 lbs.	3,050 lbs.	3,200 lbs.
Payload	4,250 lbs.	4,100 lbs.	3,950 lbs.	3,800 lbs.
Axles (Tandem)	3,500 lbs.	3,500 lbs.	3,500 lbs.	3,500 lbs.
Brakes	Electric	Electric	Electric	Electric
Tires	ST205/75D14/C	ST205/75D14/C	ST205/75D14/C	ST205/75D14/C
Wheels	5 Bolt	5 Bolt	5 Bolt	5 Bolt
Frame	6" I-Beam	6" I-Beam	6" I-Beam	6" I-Beam
Floor (24" O/C)	3/4" Plywood	3/4" Plywood	3/4" Plywood	3/4" Plywood
Side Walls (16" O/C)	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood

**G.V.W.R.** (Gross Vehicle Weight Rating)

**O/C** (On Center): Refers to the distance between each stud or joist.

**BWW** (Between the Wheel Wells)

Some trailers are shown with optional equipment.

Specifications are based on the latest information and are subject to change without notice.